






NOTE: 1
DESIGN CODE:
API 17H/6A

NOTE: 2
TECHNICAL CLASSIFICATION:
Article Type: 001-Hot Stabs
Main Group: 1.01. Ø35 Hot Stab
Intermediate Group: 1.1.02. Receptacle
Sub Group: 1.1.2.01. Single

NOTE: 3
INTERFACE INFORMATION:
Pressure Rating Bar: 690
Design Water Depth: N/A
Material: S32750 SUPER DUPLEX
Weight: 1,7 kg
Volume: 0,22 dm³
Submerged Weight: 1,5 kg
Surface Area: 320 cm²
Hydraulic: 3/8" Autoclave
Mechanical: 6xM6@PCD 66
Electrical: N/A
Com. & Protocol: N/A

NOTE: 4
ADDITIONAL INFORMATION:
The Ø35mm Blue Logic Hot Stab is made according to API 17H. This Hot Stab is in general designed for flow up to approx 25 liters pr. minute. We have pressure rating up to PSI 20K or 1380 Bar. The Hot Stab system can also be fitted with an lock-system.

Other hydraulic port interface can be delivered on customers request.



04	25.4.2014	9-IFU (Issued for Use)		WTJ	HNJ	WTJ
03	19.4.2012	Issued for Construction		LGH	EKJ	LGH
02	19.4.2012	Issued for Information		LGH	NA	NA
01	20.3.2012	Issued for Information		LGH	NA	NA
Rev.	Date	Reason for issue	Revision change	Made	Chk'd	Appr.



Dwg Scale:	NTS
Dwg Proj:	
Dwg Format:	A3

Drawing title:	Ø35 SP Rec 10k Long-term MP 3/8"
Drawing number:	BA2368
Rev.	04