



NOTE: 1  
DESIGN CODE:  
API 17H/6A

NOTE: 2  
TECHNICAL CLASSIFICATION:  
Article Type: 001-Hot Stabs  
Main Group: 1.01. Ø35 Hot Stab  
Intermediate Group: 1.1.02. Receptacle  
Sub Group: 1.1.2.02. Dual

NOTE: 3  
INTERFACE INFORMATION:  
Pressure Rating Bar: 690  
Design Water Depth: N/A  
Material: S32750 SUPER DUPLEX  
Weight in Air: 2,8 kg  
Volume: 0,35 dm<sup>3</sup>  
Submerged Weight: 2,41 kg  
Surface Area: 454 cm<sup>2</sup>  
Hydraulic: MP 3/8"  
Mechanical: 6xM6@PCD 66  
Electrical: N/A  
Com. & Protocol: N/A

NOTE: 4  
ADDITIONAL INFORMATION:  
The Ø35mm Blue Logic Hot Stab is made according to API 17H. This Hot Stab is in general designed for flow up to approx 25 liters pr. minute. We have pressure rating up to PSI 20K or 1380 Bar. The Hot Stab system can also be fitted with an lock-system.

Other hydraulic port interface can be delivered on customers request.



Rev.	Date	Reason for issue	Revision change	Made	Chk'd	Appr.
03	07.4.2024	9-IFU (Issued for Use)		HNJ	TAN	HNJ
02	24.8.2020	9-IFU (Issued for Use)		WTJ	HNJ	WTJ
01	7.11.2014	2-IFT (Issued for Tender)		HNJ	N/A	N/A

**BLUE LOGIC**

This Drawing is the Property of Blue Logic AS © and must Not be Loaned, Reproduced or Transferred to others without written Permission

Dwg Scale:	NTS
Dwg Proj:	
Dwg Format:	A3

Drawing title:	Ø35 DP Rec 10k Long-term MP 3/8"	
Drawing number:	BA5903	Rev: 03