



NOTE: 1  
DESIGN CODE:  
NS-EN 13445

NOTE: 2  
TECHNICAL CLASSIFICATION:  
Article Type: 003-Valve Stabs  
Main Group: 3.04. Ø60-Valvestab  
Intermediate Group: 3.34.01. Stab  
Sub Group: 3.34.74.3. Triple

NOTE: 3  
INTERFACE INFORMATION:  
Pressure Rating Bar: 250  
Design Water Depth:  
Material: Intervention  
Weight: 9,3 kg  
Volume: 1,29 dm<sup>3</sup>  
Submerged Weight: 8,02 kg  
Surface Area: 3384 cm<sup>2</sup>  
Hydraulic: 2x3/4" BSP - 1x 1/2" BSP  
Mechanical: N/A  
Electrical: N/A  
Com. & Protocol: N/A

NOTE: 4  
SPAREPARTS:  
BB1698

NOTE: 5  
ADDITIONAL INFORMATION:  
This VStab is only compatible with triple port Vstab receptacles. Mating of Vstabs and Vstab receptacles with different number of ports may cause injuries, equipment damage and spill of fluid.

Usermanual: 600134-TD-0004

NOTE: 6  
WEB LINK:  
<http://e-sea.bluelogic.no/main.aspx?page=article&artno=BA1135>

14	10.6.2024	9-IFU (Issued for Use)		WTJ	HNJ	WTJ
13	15.9.2023	9-IFU (Issued for Use)		HNJ	LGH	HNJ
12	15.9.2022	9-IFU (Issued for Use)		WTJ	LGH	WTJ
11	19.4.2022	9-IFU (Issued for Use)		WTJ	LGH	WTJ
Rev.	Date	Reason for issue	Revision change	Made	Chk'd	Appr.



Dwg Scale:	NTS
Dwg Proj:	
Dwg Format:	A3

Drawing title:  
Ø60 TP VStab 250Bar Interv 70deg BSP 3/4"-1/2"

Drawing number:	BA1135	Rev.	14
-----------------	--------	------	----