

NOTE: 1 DESIGN CODE: NOTE: 2 **TECHNICAL CLASSIFICATION:** Article Type: 006-El. Connectors Main Group:6.01. Subsea USBIntermediate Group:6.28.01. 0-60W Subsea USB Sub Group: 6.28.95.01. Male Connector NOTE: 3 INTERFACE INFORMATION: Pressure Rating Bar: N/A Design Water Depth: N/A Material: N/A 0,5 kg 0,37 dm^3 Submerged Weight: 0,15 kg Surface Area: 2244 cm^2 Hydraulic: N/A Mechanical: N/A Electrical: N/A Com. & Protocol: N/A

## NOTE: 4

**OPERATION & MAINTENANCE INFORMATION:** 600128-TD-0020

ADDITIONAL INFORMATION:

Inductive Subsea Connector for transfer of electrical power and communication. The Blue Logic inductive connector is a multipurpose electrical connector with the capacity of transferring up to 50W electrical power, 80Mbps Ethernet and 230kbps serial communication on RS232 or RS485. BB9046 is a male connector, configured to be the secondary side (receiving part) in a connector system. Designed to act as test-interface towards primary side inductive connectors in workshop environment, not suitable for submerged service.

## USB-A 50W Secondary Test Unit