



NOTE: 2
TECHNICAL CLASSIFICATION:
Article Type: 001-Hot Stabs
Main Group: 1.01. Ø35 Hot Stab
Intermediate Group: 1.1.02. Receptacle
Sub Group: 1.1.2.02. Dual

NOTE: 3

INTERFACE INFORMATION:

Pressure Rating Bar: 690

Design Water Depth: N/A

Material: S32750 SUPER DUPLEX

Weight in Air: 2,8 kg

Volume: 0,35 dm³

Submerged Weight: 2,41 kg

Surface Area: 454 cm²

Hydraulic: MP 3/8"

Mechanical: 6xM6@PCD 66

Electrical: N/A

Com. & Protocol: N/A

NOTE: 4
ADDITIONAL INFORMATION:
 The Ø35mm Blue Logic Hot Stab is made according to API 17D. This Hot Stab is in general designed for flow up to approx 25 liters pr. munute. We have pressure rating up to PSI 20K or 1380 Bar. The Hot Stab system can also be fitted with an lock-system.

All Blue Logic Receptacles is Standardized with BSP Interface.
NPT and MP (Autoclave or Similar) Interfaces can be delivered
upon request.



							<div>BLUE LOGIC</div> 	Unless Noted Otherwise:	Dwg. Scale: NTS	Drawing title: Ø35 DP Rec 10k Long-term MP 3/8"			
03	25.1.2024	7-IFC (Issued for Construction)		HNJ	TAN	HNJ		Dim. Tol: NS-ISO 2768-1	Dwg Proj: 				
02	24.8.2020	9-IFU (Issued for Use)		WTJ	HNJ	WTJ		Roughness: Ra	Dwg Format: A3				
01	7.11.2014	2-IFT (Issued for Tender)		HNJ	N/A	N/A		Fillet Rad: Corner Rmax:	Break Edges: (R. Alt. 45°) R= 0.1-0.5	Drawing number: BA5903			Rev. 03
Rev.	Date	Reason for issue	Revision change	Made	Chk'd	Appr.							