



NOTE: 1 DESIGN CODE: API 17H/6A

NOTE: 2

TECHNICAL CLASSIFICATION:
Article Type: 001-Hot Stabs
Main Group: 1.01. Ø35 Hot Stab
Intermediate Group: 1.1.01. Stab
Sub Group: 1.1.1.02. Dual

NOTE: 3

INTERFACE INFORMATION:
Pressure Rating Bar: 690
Design Water Depth: N/A
Material: Intervention
Weight in Air: 9,2 kg
Volume: 3,13 dm^3
Submerged Weight: 6,02 kg
Surface Area: 9877 cm^2
Hydraulic: 3/8" BSP

Electrical: Subconn BCR2410F Com. & Protocol: RS232/Ethernet

N/A

NOTE: 4

Mechanical:

ADDITIONAL INFORMATION:

Multi-interface coupler for transferring electrical power, data communication and hydraulic power. The unit consist of a Blue Logic standard Dual Port Hot Stab with integrated 250W Inductive Connector. Allows for quick connection and disconnection of electric and hydraulic interface in one go. Ideal for subsea connection of ROV tooling with both electrical and hydraulic functions/features. This is the male part intended for installation on the ROV.

02	15.2.2021	9-IFU (Issued for Use)		WTJ	HNJ	WTJ			
01	8.2.2021	9-IFU (Issued for Use)		WTJ	KOS	WTJ			
Rev.	Date	Reason for issue	Revision change	Made	Chk'd	Appr.			



Dwg Scale:	Drawing title:	
NTS	Ø35 DP Stab 10k w250W Inductive Connector	
Dwg Proj:	233 DI Glab Tok W230W Illidactive Collifector	
Dwg Format: A3		
Λ3	Drawing number:	Rev.
	DDS9/12	02