



NOTE: 1  
DESIGN CODE:  
API 17H/6A

NOTE: 2  
TECHNICAL CLASSIFICATION:  
Article Type: 001-Hot Stabs  
Main Group: 1.01. Ø35 Hot Stab  
Intermediate Group: 1.1.02. Receptacle  
Sub Group: 1.1.2.04. Quad

NOTE: 3  
INTERFACE INFORMATION:  
Pressure Rating Bar: 690  
Design Water Depth: N/A  
Material: S32750 SUPER DUPLEX  
Weight: 4,1 kg  
Volume: 0,52 dm<sup>3</sup>  
Submerged Weight: 3,53 kg  
Surface Area: 690 cm<sup>2</sup>  
Hydraulic: BSP 1/2"  
Mechanical: 6xM6@PCD 66  
Electrical: N/A  
Com. & Protocol: N/A

NOTE: 4  
ADDITIONAL INFORMATION:  
The Ø35mm Blue Logic Hot Stab is made according to API 17D. This Hot Stab is in general designed for flow up to approx 25 liters pr. munute. We have pressure rating up to PSI 20K or 1380 Bar. The Hot Stab system can also be fitted with an lock-system.

All Blue Logic Receptacles is Standardized with BSP Interface.  
NPT and MP (Autoclave or Similar) Interfaces can be delivered upon request.



07	25.4.2014	9-IFU (Issued for Use)		WTJ	HNJ	WTJ
06	7.2.2013	7-IFC (Issued for Construction)		LAE	LGH	LAE
05	25.11.2011	Issued for Construction		LGH	NA	NA
04	3.10.2011	As Built		LGH	NA	NA
Rev.	Date	Reason for issue	Revision change	Made	Chk'd	Appr.

**BLUE LOGIC**

Dwg Scale:  
NTS  
Dwg Proj:  
Dwg Format:  
A3

Drawing title:  
Ø35 QP Rec 10k Interv BSP 1/2"

Drawing number:  
PA0095

Rev.  
07