



NOTE: 1
DESIGN CODE:
API 17H/6A

NOTE: 2
TECHNICAL CLASSIFICATION:
Article Type: 001-Hot Stabs
Main Group: 1.01. Ø35 Hot Stab
Intermediate Group: 1.1.02. Receptacle
Sub Group: 1.1.2.02. Dual

NOTE: 3
INTERFACE INFORMATION:
Pressure Rating Bar: 690
Design Water Depth: N/A
Material: S32750 SUPER DUPLEX
Weight: 2,3 kg
Volume: 0,29 dm³
Submerged Weight: 1,99 kg
Surface Area: 432 cm²
Hydraulic: BSP 1/2"
Mechanical: 6xM6@PCD 66
Electrical: N/A
Com. & Protocol: N/A

NOTE: 4
ADDITIONAL INFORMATION:
The Ø35mm Blue Logic Hot Stab is made according to API 17D. This Hot Stab is in general designed for flow up to approx 25 liters pr. minute. We have pressure rating up to PSI 20K or 1380 Bar. The Hot Stab system can also be fitted with an lock-system.

All Blue Logic Receptacles is Standardized with BSP Interface.
NPT and MP (Autoclave or Similar) Interfaces can be delivered upon request.



| | | | | | | |
|------|-----------|---------------------------------|-----------------|------|-------|-------|
| 05 | 25.4.2014 | 9-IFU (Issued for Use) | | WTJ | HNJ | WTJ |
| 04 | 11.2.2013 | 7-IFC (Issued for Construction) | | LAE | HNJ | LAE |
| 03 | 7.2.2013 | 7-IFC (Issued for Construction) | | LAE | LGH | LAE |
| 02 | 3.10.2011 | Issued for Construction | | LGH | EKJ | LGH |
| Rev. | Date | Reason for issue | Revision change | Made | Chk'd | Appr. |

BLUE LOGIC

| | |
|-------------|-----|
| Dwg Scale: | NTS |
| Dwg Proj: | |
| Dwg Format: | A3 |

| | | | |
|-----------------|--------------------------------------|--|---------|
| Drawing title: | Ø35 DP Rec 10k Interv BSP 1/2" ID8mm | | |
| Drawing number: | PA0174 | | Rev. 05 |