



NOTE: 1
DESIGN CODE:
API 17H/6A

NOTE: 2
TECHNICAL CLASSIFICATION:
Article Type: 001-Hot Stabs
Main Group: 1.01. Ø35 Hot Stab
Intermediate Group: 1.1.02. Receptacle
Sub Group: 1.1.2.02. Dual

NOTE: 3
INTERFACE INFORMATION:
Pressure Rating Bar: 1380
Design Water Depth: N/A
Material: Nitronic 50 UNS20910
Weight: 4,7 kg
Volume: 0,6 dm³
Submerged Weight: 4,13 kg
Surface Area: 579 cm²
Hydraulic: BSP 3/8"
Mechanical: 6xM6@PCD 66
Electrical: N/A
Com. & Protocol: N/A

NOTE: 4
ADDITIONAL INFORMATION:
The Ø35mm Blue Logic Hot Stab is made according to API 17D. This Hot Stab is in general designed for flow up to approx 25 liters pr. munute. We have pressure rating up to PSI 20K or 1380 Bar. The Hot Stab system can also be fitted with an lock-system.

All Blue Logic Receptacles is Standardized with BSP Interface.
NPT and MP (Autoclave or Similar) Interfaces can be delivered upon request.



Rev.	Date	Reason for issue	Revision change	Made	Chk'd	Appr.
03	3.6.2014	6-IFC (Issued for Construction)		WTJ	HNJ	WTJ
02	3.10.2011	6-IFC (Issued for Construction)		VFA	EKJ	LGH

BLUE LOGIC

Dwg Scale:
NTS
Dwg Proj:
Dwg Format:
A3

Drawing title:
Ø35 DP Rec 20K Interv BSP 3/8"

Drawing number:
PA0429

Rev.
03