



NOTE: 1  
STANDARDS:  
N/A

NOTE: 2  
INTERFACE INFORMATION:  
Hydraulic: 3/8" BSP  
Mechanical: N/A  
Electrical: N/A  
Data Com.: N/A

NOTE: 3  
PROPERTIES:  
Material Class: N/A  
Temperature Class: N/A  
Rated Work Press Bar: 4,15  
Test Pressure: N/A  
Specification Level: N/A  
Flow Rate: N/A  
Qualification: N/A  
Application: N/A  
Load Rating: N/A  
Torque Rating: N/A  
Design Water Depth: N/A  
Weight in Air: 0,1 kg  
Volume: 0,01 dm<sup>3</sup>  
Submerged Weight: 0,05 kg

NOTE: 4  
WEB LINK:  
<http://e-sea.bluelogic.no/main.aspx?page=article&artno=BA5814>

NOTE: 5  
ADDITIONAL INFORMATION:  
These Relief Valves can be delivered with various cracking pressure on customers request.  
Standard temperature rating 0-60 °C  
Fluid: hydraulic oils.  
This Valve is typical made for use as safety pressure relief.  
For other fluids and temp range, confer with Blue Logic.



Rev.	Date	Reason for issue	Revision change	Made	Chk'd	Appr.
03	17.1.2022	9-IFU (Issued for Use)		WTJ	HNJ	WTJ
02	28.3.2017	9-IFU (Issued for Use)		WTJ	HNJ	WTJ
01	23.10.2014	9-IFU (Issued for Use)		LGH	N/A	N/A

**BLUE LOGIC**

This Drawing is the Property of Blue Logic AS © and must Not be Loaned, Reproduced or Transferred to others without written Permission

Dwg Scale:	NTS
Dwg Proj:	
Dwg Format:	A3

Drawing title:	Relief Valve 60psi 3/8" BSP
Drawing number:	BA5814
Rev:	03