



NOTE: 1  
STANDARDS:  
NA

NOTE: 2  
INTERFACE INFORMATION:  
Hydraulic: 3/8" BSP  
Mechanical: NA  
Electrical: N/A  
Data Com.: NA

NOTE: 3  
PROPERTIES:  
Material Class: FF  
Temperature Class: NA  
Rated Work Press Bar: 0,8  
Test Pressure: NA  
Specification Level: NA  
Flow Rate: NA  
Qualification: NA  
Application: Intervention  
Load Rating: NA  
Torque Rating: NA  
Design Water Depth: 3000m  
Weight in Air: 0,1 kg  
Volume: 0,01 dm<sup>3</sup>  
Submerged Weight: 0,05 kg

NOTE: 4  
WEB LINK:  
<http://e-sea.bluelogic.no/main.aspx?page=article&artno=BA1382>

NOTE: 5  
ADDITIONAL INFORMATION:  
These Relief Valves can be delivered with various cracking pressure on customers request.  
Standard temperature rating 0-60 °C  
Fluid: hydraulic oils.  
This Valve is typical made for use as safety pressure relief.  
For other fluids and temp range, confer with Blue Logic.



07	28.6.2023	9-IFU (Issued for Use)		LGH	TAN	LGH	<div><div>BLUE LOGIC</div><div></div></div> <div><small>This Drawing is the Property of Blue Logic AS © and must Not be Loaned, Reproduced or Transferred to others without written Permission</small></div>	Dwg Scale: NTS		Drawing title: Relief Valve 0,8 Bar 3/8" BSP	Drawing number: BA1382	Rev. 07
06	17.1.2022	9-IFU (Issued for Use)		WTJ	HNJ	WTJ		Dwg Proj:				
05	28.3.2017	9-IFU (Issued for Use)		WTJ	HNJ	WTJ		Dwg Format: A3				
04	30.3.2016	9-IFU (Issued for Use)		WTJ	HNJ	WTJ						
Rev.	Date	Reason for issue	Revision change	Made	Chk'd	Appr.						