

WTJ BNE LGH

WTJ LGH WTJ

Made Chk'd Appr.

01A 23.5.2023

01 21.2.2023

7-IFC (Issued for Construction)

Reason for issue

Revision change

NOTE: 1 **DESIGN CODE:** API17H, API17F, TR1231, TR1233

NOTE: 2

Application: Permanent Design Water Depth: 3000 Weight in Air: 32,1 kg 5,74 dm^3 Volume: Submerged Weight: 26,23 kg

NOTE: 3

ADDITIONAL INFORMATION:

300W Inductive Connector for wireless transfer of power and communication. Designed for installation in Blue Logic's Charging Station,

for charging of underwater intervention drones.

Metallic parts in Super Duplex suitable for permanent installation.

The Connector is made SWiG compatible and fully compliant to API17F, API 17H, and to Equinor TR1231 Appendix D.

A new MK3 Flange Iterface for Pressure Balanced Oil Filled (PBOF) Hose attachment has been included and qualified. This makes it possible to interface any type of equipment.

Input Volt 400 VDC +/- 10% Output Volt 325VDC +/-5% Output current 1,1A Efficiency @350W 86% Start-up time 100 sec.

Connector shall NOT be connected to a CP-System as described in Installation Manual, ref.: 500419-TD-0015

Available Interfaces (can be configured). See Datasheet for details, ref.: 500419-TD-0017

	,
ID	
1	+ 400 VDC Filter In
2	0 VDC Filter in
3	Chassis
4	RS232 Config GND
5	RS232 Config TX
6	RS232 Config RX
7	L3-E Eth2 TX+ Transparent
8	L3-F Eth2 TX- Transparent
9	L3-I Eth2 RX+ Transparent
10	L3-J Eth2 RX- Transparent
	Optional:
11	L3-G Eth1 TX+ Config.
12	L3-H Eth1 TX- Config.
13	L3-K Eth1 RX+ Config.
14	L3-L Eth1 RX- Config.