

Revision change

Reason for issue

Rev Date

DESIGN CODE: DVN/GL-ST-E273 NOTE: 2 TECHNICAL CLASSIFICATION: Article Type: 016-MultiDog Main Group: 16.02. 3-13.5 WLL Intermediate Group: 16.71.01. Lifting Sub Group: 16.71.343.01. Male NOTE: 3 INTERFACE INFORMATION: Pressure Rating Bar: N/A

Design Water Depth: N/A Material: N/A Weight: 20,4 kg Volume: 3,5 dm^3 Submerged Weight: 16,86 kg Surface Area: 5099 cm^2 Hydraulic: N/A Mechanical: N/A Electrical: N/A Com. & Protocol: N/A

NOTE: 4

ADDITIONAL INFORMATION:

The ROV operated MultiDog connector is fully field configurable making it suitable for most subsea deployment and recovery strategies. The lifting connector has a standardized interface that can be used for pull-in, installation/removal of light template protection covers, treecaps and other light intervention modules.

The MultiDog has a capacity of 13,5 ton WLL and can be fieldconfigured to interface soft lines, pad-eyes and wire ropes.

The MultiDog lifting tool is ROV friendly, reusable and can be deployed at any depth providing a backup release system in the unlikely event of failure.

Fail-safe design prevents the connector from being released under load.

MultiDog Lifting 13,5 WLL Male Mech 3 Dog v2

Drawing num BB2067